



TILE LEVELING SYSTEM

- Consistently spaces tile and removes lippage
- Great for larger wall and floor tiles up to 14 mm thick
- After thinset has dried, use a rubber mallet to hit the system in line with the grout joint
- Wedges are reusable
- For tight, level tiles, use the PLS Pliers (**BWTLSP**)



**200 packs sold in resealable bag,
bulk packs sold in boxes**



1

Place spacer



2

Insert wedge



3

Tighten & let mortar dry



4

Remove

EDI	Part#	Description	Size-in	Size-mm	Qty	Inner/Outer
33062	HDWTLS	PLS Max Wedges	N/A	N/A	200	1/6
33064	HDWTLS3	PLS Max Straight Spacer Bases	1/8	3	200	1/6
33066	HDWTLS15	PLS Max Straight Spacer Bases	1/16	1.5	200	1/6
41831	WPLSMAX500	PLS Max Wedges - Bulk Box	N/A	N/A	500	1/1
41833	3PLSMAX1000	PLS Max Straight Spacer Bases - Bulk Box	1/8	3	1000	1/1
41835	15PLSMAX1000	PLS Max Straight Spacer Bases - Bulk Box	1/16	1.5	1000	1/1

Compatible PLS Accessories:



**Anti-Scratch Disk to avoid scuffing
DSPIN100 | EDI-41796**



**PLS Pliers for tightening
BWTLSP | EDI-33060**



BARWALT®
A MARSHALLTOWN® BRAND