


# SHOCKWAVE 2.0 POWER SCREED

- Less labor intensive than a traditional hand screed
- Consolidates concrete, resulting in a stronger slab
- Excellent vibration dampening (little vibration passed on to operator)
- Throttle lever does not require constant contact
- Direct drive shaft for extended life (no bending in shaft between motor and eccentric weight)
- Fully adjustable handlebars and grips
- Onboard hour meter (great for rental and scheduled maintenance)
- Bolt-on kickstand keeps unit upright when not in-use
- Forward mounting 9" hole spacing is compatible with most competitor power screed blades
- Unique frame design provides superior engine protection and makes for easy transportation
- Honda GX35 Engine
- Sold 1 per inner pack/1 per outer pack



Adjustable handlebars and grips



Accessible handles for easy lifting



Hour meter

## Shockwave™ 2.0 Screed Boards

- L-shaped board is ideal for wet screeding and works well for form-to-form screeding
- 9" hole spacing that fits most competitor models
- Constructed of aluminum alloy engineered to withstand prolonged vibration
- Option for one or two-hole mounting on 16' board for attaching one or two Power Screeds
- Boards 10' and longer ship LTL
- Sold 1 per inner pack/1 per outer pack

EDI	Part#	Description
32856	SW200H	Shockwave™ 2.0 Vibratory Screed - Gas Engine

Shockwave™ 2.0 Screed Boards						
EDI	Part#	Description	Size-ft.	Size-M	Weight-lbs/ kg	
32403	32403	9" Hole Spacing Blade-4'	4	1.2	8 / 36	
32404	32404	9" Hole Spacing Blade-4.5'	4.5	1.37	9 / 41	
32405	32405	9" Hole Spacing Blade-6'	6	1.8	11.6 / 5.3	
32406	32406	9" Hole Spacing Blade-8'	8	2.4	15.9 / 7.2	
32407	32407	9" Hole Spacing Blade-10'	10	3.0	20.1 / 9.1	
32408	32408	9" Hole Spacing Blade-12'	12	3.7	24.4 / 11.1	
32409	32409	9" Hole Spacing Blade-14'	14	4.3	28.4 / 13	
32410	32410	9" Hole Spacing Blade-16'	16	4.9	32.9 / 15	
32411	32411	9" Hole Spacing Double Mount	16	4.9	32.9 / 15	

\*Compatible with most competitor power screeds